

Écran de bureau

NEC MULTISYNC EA272F



NEC MultiSync

- In-demand display size – the popular 27.0" display with Full HD resolution is the perfect size for busy office workspaces.
- Clutter-free workspace – Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable.
- Future-proof flexibility – wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.
- Easy multi-screen set-up – Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed.
- Maximum attention to health and well-being – with outstanding ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.

Spécifications

Technologie du panneau	AH-IPS LCD with LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m2)	250
Taux de contraste	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Couleurs d'affichage	16.78
Temps de réponse (moy. gris à gris) ms	6
Taille de pixel (mm H x L)	0,311
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 15 kWh/1000 h, Energy efficiency class: D, Human sensor, LED backlight technology
Ecological Standards	Design conçu pour une réduction du carton d'emballage, Utilisation minimale de matériaux nocifs
Ecological Materials	ErP compliant, WEEE
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	527
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Température de fonctionnement (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C
Analog	VGA
Taille du b�zel (G/D) mm	1
Taille du b�zel (H) mm	1
Taille du b�zel (B) mm	16
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

Colour Versions	Fa�ade noir, Bo�tier noir, Fa�ade blanc, Bo�tier blanc
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Prise casque jack, Haut-parleurs int�gr�s (1 W + 1 W)
Adjust Functions	Audio Volume/Lock-Out, Ajustement automatique, Luminosit�, Contr�le des couleurs, Contraste, Control Sync, Mode DV, Mode Eco, Factory Preset, Fine Adjust (analog), Human Sensing, Gestion intelligente de la consommation, Choix de la langue, Informations sur l'�cran, NTAA (Non-Touch-Auto-Adjustment), Menu � l'�cran (On-Screen-Display) verrouill�, R�cup�ration � l'aide d'une seule touche, Minuteur de mise hors tension, sRGB
Safety & Ergonomics	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, T�V Ergonomics, T�V GS, UL/C-UL or CSA, TCO Edge 2
Garantie limit�e du fabricant (ans)	3 ans y compris r�tro-�clairage, En option 4. + 5 ann�e(s) d'extension de garantie
Special Characteristics	DDC/CI compatible, RGB, Frame Comp, PJLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touches avec capteur tactile, USB ver. 3.0 (3 t�l�d�chargement / 1 t�l�chargement)
Accessoires	
Shipping Content	C�ble Control Sync, C�ble DisplayPort, Monitor, Cordon d'alimentation, Manuel de configuration, Guide de configuration, C�ble USB, C�ble USB-C
Taille diagonale (cm)	27
Taille diagonale (cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Consommation �nerg�tique en fonctionnement (IEC62087:2012)	15 (Eco Mode 2), 21 (typ.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Montage (VESA/Nombre de points/Espacement mm)	100 x 100
Verrou Kensington	True

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Poids du produit avec le pied (Kg)	9
------------------------------------	---



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: NEC MultiSync EA272F, 22/6/2026