

Écran de bureau

Sharp/ NEC MultiSync® E244FL



For driving down costs without compromising quality, the E-series prioritises user comfort and productivity making it an excellent solution for both the home office and for small to medium sized businesses for general office applications.

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

Spécifications

| | |
|--|--|
| Technologie du panneau | VA TFT with W-LED backlight |
| Rapport d'aspect | 16:9 |
| Luminosité (cd/m ²) | 250 |
| Taux de contraste | 1000:1 |
| Couleurs d'affichage | 16.77 |
| Temps de réponse (moy. gris à gris) ms | 6 |
| Taille de pixel (mm H x L) | 0,275 |
| Viewing Angle [°] | 178 |
| <hr/> | |
| Height adjustable stand [mm] | 120 |
| Screen Rotate [°] | -90 - 90 |
| [AVSpecificationLandscapeDimensionsWidthMm] | 610 |
| [AVSpecificationLandscapeDimensionsDepthMm] | 283 |
| [AVSpecificationLandscapeDimensionsHeightMinMm] | 377 |
| [AVSpecificationLandscapeDimensionsHeightMaxMm] | 507 |
| <hr/> | |
| Digital | DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up) |
| Output Control | 1 x RJ45 |
| <hr/> | |
| Taille du biseau (G/D) mm | 1 |
| Taille du biseau (H) mm | 16 |
| Taille du biseau (B) mm | 16 |
| <hr/> | |
| Poids du produit sans le pied (Kg) | 5 |
| Poids du produit avec le pied (Kg) | 8 |
| <hr/> | |
| Taille diagonale (cm) | 24 |
| Taille diagonale (cm) | 60 |
| <hr/> | |
| Consommation énergétique en fonctionnement (IEC62087:2012) | 13 (Eco Mode 2), 19 (typ.) |
| Power Supply | Integrated Power Supply |
| <hr/> | |
| Special Characteristics | Low Blue Light, Local dimming |

| | |
|---|---|
| Colour Versions | Façade noir, Boîtier noir, Façade blanc, Boîtier blanc |
| Cable Management | True |
| Plug & Play | VESA DDC2Bi |
| Audio | 1W + 1W (De-activateable), Prise casque jack |
| Safety & Ergonomics | EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE |
| Garantie limitée du fabricant (ans) | 3 ans y compris rétro-éclairage |
| <hr/> | |
| Température de fonctionnement (oC) | 5 - 35 |
| Storage Temperature [°C] | -10 - 60 |
| Storage Humidity [%] | 10 |
| Storage Humidity [%] | 85 |
| <hr/> | |
| Accessoires | |
| Shipping Content | Câble DisplayPort, Cordon d'alimentation, Guide de configuration, Câble USB-C |
| <hr/> | |
| Energy Efficiency | Carbon Footprint Meter / Carbon Savings Meter, ECOMode |
| Ecological Standards | RoHS compliant, TCO 9.0 |
| <hr/> | |
| Montage (VESA/Nombre de points/Espacement mm) | 100 x 100 |
| Verrou Kensington | True |
| <hr/> | |
| Horizontal Frequency [kHz] | 31.5 - 81 |
| Vertical Frequency [Hz] | 50 - 75 |
| <hr/> | |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |
| <hr/> | |
| Optimum Resolution | 1920 x 1080 at 60 Hz |

