

Écran de bureau

SHARP/ NEC MULTISYNC EA271U



NEC MultiSync

- Newest USB Type-C connectivity standard – optimize connectivity and replace video, audio, power and USB cabling with just a single cable to connect your notebook/tablet PC with the display.
- Maximum attention to health and well-being – with outstanding ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.
- Ease of multi-display control – manage the settings of up to 8 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Spécifications

Technologie du panneau	IPS TFT with W-LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m2)	350
Taux de contraste	1300:1
[AVSpecificationDynamicContrastRatio]	9000:1
Couleurs d'affichage	1064.64
Temps de réponse (moy. gris à gris) ms	5
Taille de pixel (mm H x L)	0,155
Viewing Angle [°]	178
Special Characteristics	Capteur de lumière ambiante pour des niveaux de luminosité optimisés, ControlSync®, Personnaliser le réglage, DDC/CI compatible, Modes Eco, Frame Comp, ErgoDesign®, Height adjustable stand (150 mm) with 90° Pivot features, Human Sensor, LED Backlight Technology, Picture-by-Picture, Poignée et pied quick-release, Versatile and easy installation (VESA standard) with NaViSet and NaViKey
Energy Efficiency	Ambient light sensor, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 22 kWh/1000 h, Energy efficiency class: F, Human sensor, LED backlight technology
Ecological Standards	Utilisation minimale de matériaux nocifs
Ecological Materials	Energy Star 8.0, ErP compliant, RoHS compliant, TCO 8.0
Température de fonctionnement (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Taille diagonale (cm)	27
Taille diagonale (cm)	68
Colour Gamuts	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
Digital	DisplayPort, USB Type C (60 W), HDMI, USB ver. 3.1 (3 down / 1 up)
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75
Taille du biseau (G/D) mm	1
Taille du biseau (H) mm	1

Colour Versions	Façade noir, Boîtier noir, Façade blanc, Boîtier blanc
Cable Management	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	1W + 1W (De-activateable), Prise casque jack
Adjust Functions	Mode DV, Mode Eco, Human Sensing, Gestion intelligente de la consommation, sRGB
Safety & Ergonomics	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Garantie limitée du fabricant (ans)	3 ans y compris rétro-éclairage, Optional 1st to 3rd year 24/7 usage warranty, En option 4. + 5 année(s) d'extension de garantie

Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160

Accessoires

Shipping Content	Câble Control Sync, Affichage, Câble DisplayPort, Cordon d'alimentation, Manuel de configuration, Câble USB
------------------	---

Consommation énergétique en fonctionnement (IEC62087:2012)	150 (max.), 30 (Eco Mode 1), 38 (Eco Mode 2), 38 (shipping)
Power Supply	1.6 A/0.75 A, 100-240 V, Integrated Power Supply

Montage (VESA/Nombre de points/Espacement mm)	100 x 100
Verrou Kensington	True

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Poids du produit avec le pied (Kg)	10
------------------------------------	----



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271U, 22/6/2026