

Écran de bureau

SHARP/ NEC MULTISYNC EA271F



NEC MultiSync

- Ergonomic Office – full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.
- Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.
- Maximise image quality with Uniformity Control – benefit from perfect uniformity across multi-screen setups with just one click in the display's on-screen menu.

Spécifications

Technologie du panneau	AH-IPS LCD with LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m ²)	250
Taux de contraste	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Couleurs d'affichage	16.78
Temps de réponse (moy. gris à gris) ms	6
Taille de pixel (mm H x L)	0,311
Special Characteristics	ControlSync®, Carbon Savings Meter, Préréglage DICOM, Personnaliser le réglage, DDC/CI compatible, RGB, Frame Comp, ErgoDesign®, LED Backlight Technology, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touches avec capteur tactile, USB ver. 3.0 (3 télédéchargement / 1 téléchargeement), Flicker Free
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 11 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Ecological Standards	Design conçu pour une réduction du carton d'emballage, Utilisation minimale de matériaux nocifs
Ecological Materials	Energy Star 8.0, ErP compliant, TCO 8.0, WEEE
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768, 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Accessoires	
Shipping Content	Câble Control Sync, Câble DisplayPort, Monitor, Cordon d'alimentation, Manuel de configuration, Guide de configuration, Câble USB
Consommation énergétique en fonctionnement (IEC62087:2012)	12 (Eco Mode 2), 17 (Eco Mode), 17 (typ.), 45 (max.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Poids du produit sans le pied (Kg)	5
Poids du produit avec le pied (Kg)	8

Colour Versions	Façade noir, Boîtier noir, Façade blanc, Boîtier blanc
Cable Management Plug & Play	True DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Prise casque jack, Haut-parleurs intégrés (1 W + 1 W) Audio Volume/Lock-Out, Ajustement automatique, Luminosité, Contrôle des couleurs, Contraste, Control Sync, Mode DV, Mode Eco, Factory Preset, Fine Adjust (analog), Human Sensing, Gestion intelligente de la consommation, Choix de la langue, Informations sur l'écran, NTAA (Non-Touch-Auto-Adjustment), Menu à l'écran (On-Screen-Display) verrouillé, Récupération à l'aide d'une seule touche, Minuteur de mise hors tension, sRGB
Adjust Functions	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Safety & Ergonomics	3 ans y compris rétro-éclairage, Optional 1st to 3rd year 24/7 usage warranty, En option 4. + 5 année(s) d'extension de garantie
Garantie limitée du fabricant (ans)	MDSVSENSOR Value
Optional Accessories	
Height adjustable stand [mm]	150
Screen Swivel [°]	-170 - Value
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	653
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Température de fonctionnement (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Taille diagonale (cm)	27
Taille diagonale (cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Digital	DisplayPort, DVI-D, HDMI, USB ver. 3.1 (3 down / 1 up)
Analog	VGA

Montage (VESA/Nombre de points/Espacement mm)	100 x 100
Verrou Kensington	True
<hr/>	
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
<hr/>	
Taille du b�zel (G/D) mm	1
Taille du b�zel (H) mm	1



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners.  Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271F, 23/6/2026