

Projecteurs

Sharp / NEC P603X Projector



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- High brightness – for best performance in bright ambient light.
- Minimized cost of ownership – due to long lamp life and filter exchange intervals.
- Peace of Mind – with future-proof connectivity.
- Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Spécifications

Méthode de connexion du PC	XGA 1024x768
[AVSpecificationVideoColourStandards]	PAL 60, PAL N, PAL M, SECAM, NTSC (MHz) 3.58, NTSC (MHz) 4.44
Accessoires	
[AVSpecificationAccessories]	Télécommande, Manuel d'instruction (CD-ROM), Câble d'alimentation
[AVSpecificationDataTerminalsIn]	HDMI, 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)
[AVSpecificationVideoTerminals]	S-Video (Y/C), HDMI
[AVSpecificationControlTerminals]	RS232C

[AVSpecification3LcdPanel]	True
[AVSpecificationWeightKg]	4,7
[AVSpecificationLuminanceEcoModeAnsiLumen]	3600
[AVSpecificationLuminanceStandardAnsiLumen]	6000
[AVSpecificationProjectionLampW]	330
[AVSpecificationLampLifetimeEcoModeH]	8000
[AVSpecificationLampLifeStandardH]	4000
[AVSpecificationFanEcoDb]	34
[AVSpecificationFanStandardDb]	37
[AVSpecificationChangeableLens]	True
[AVSpecificationZoomLensManual]	True
[AVSpecificationLensShiftH]	True
[AVSpecificationLensShiftV]	True
[AVSpecificationKeystoneManual]	True
[AVSpecificationHFrequencekhz]	15 - 100
[AVSpecificationVFrequenceHz]	50 - 120
[AVSpecificationAudioTerminals]	Entrée / Sortie Mini Jack (3,5 mm), Entrée / Sortie RCA-Stereo, Via port HDMI
Résolution native (Pixels)	1024 x 768 (XGA)
Taux de contraste	20000:1

