

Écran de bureau

MULTISYNC E224F



- Cost and time saving operation – based on an intuitive OSD design making set-up simpler.
- Ergonomic Office – full height adjustability (120 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Black and white colour versions – white is considered to reduce the impression of tunnel vision when placed in front of a white background such as office walls.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, protecting users eyes.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

Spécifications

Technologie du panneau	VA TFT with W-LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m2)	250
Taux de contraste	3000:1
Taille de pixel (mm H x L)	0,249
Response Time (typ.) [ms]	6

Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	120
Screen Swivel [°]	-170 - 170
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	493
[AVSpecificationLandscapeDimensionsHeightMm]	483
[AVSpecificationLandscapeDimensionsDepthMm]	233

Accessoires

Shipping Content	Cordon d'alimentation, Câble DisplayPort, Guide de configuration
------------------	--

Poids du produit sans le pied (Kg)	3
Poids du produit avec le pied (Kg)	5

Montage (VESA/Nombre de points/Espacement mm)	100 x 100
---	-----------

Verrou Kensington	True
-------------------	------

Digital	DisplayPort, HDMI
Analog	D-sub 15 pin

Taille du biseau (G/D) mm	3
Taille du biseau (B) mm	17

Power Supply	Integrated Power Supply
--------------	-------------------------

Colour Versions	Façade noir, Boîtier noir, Façade blanc, Boîtier blanc
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Prise casque jack

Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free 3 ans y compris rétro-éclairage
---------------------	--

Garantie limitée du fabricant (ans)

Température de fonctionnement (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)

Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant

Taille diagonale (cm)	22
Colours [Mio.]	16

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Vertical Frequency [Hz]	50 - 75
-------------------------	---------

Optimum Resolution	1920 x 1080 at 60 Hz
--------------------	----------------------

