



- ▶ PRINT, COPY, SCAN, FAX, FILE
- ▶ PAGES PER MINUTE: 35 B/W 35 COLOUR
- ▶ PAPER CAPACITY: STD 1100 MAX 5600 SHEETS
- ▶ DUPLEX SINGLE PASS FEEDER DSPF AND FULL-COLOUR NETWORK SCANNING
- ▶ OPTIONAL FIERY PRINT CONTROLLER FOR ADVANCED NETWORK PRINTING SOLUTIONS
- ▶ INDUSTRY-LEADING SECURITY SOLUTIONS FOR ULTIMATE DATA/DOCUMENT PROTECTION
- ▶ SHARP OPEN SYSTEMS ARCHITECTURE OSA™ LETS THIRD PARTY DEVELOPERS TO CREATE CUSTOM APPLICATIONS THAT LINK THE MFP TO SOFTWARE PROGRAMMES ON A SERVER OR PC

Colour is a powerful communication tool that can give your business an extra edge in getting your message through. With the MX-3501N, you can bring the advantages of colour to your office without compromising productivity or quality. Fast output speeds for colour and black & white documents, high-quality imaging technology and a host of productivity-boosting features make copy/print jobs effortless. And with the optional Fiery Print Controller, your entire office can benefit from powerful network printing solutions.

## GÉNÉRAL

- ▶ Vitesse de production couleur ppm (A4): **35**
- ▶ Vitesse de production N&B ppm (A4): **35**
- ▶ Vitesse de production couleur ppm (A3): **17**
- ▶ Vitesse de production N&B ppm (A3): **17**
- ▶ Format papier: min.-max.: **A3W - A5R**
- ▶ Grammage papier (g/m2): **55-209**
- ▶ Capacité papier: std (feuilles): **1100**
- ▶ Capacité papier: max. (feuilles): **5600**
- ▶ Préchauffage (sec.): **240**
- ▶ Mémoire globale min/max (Mo): **768**
- ▶ Mémoire impression min/max (Mo): **640**
- ▶ Disque dur: **STD**
- ▶ Disque dur (Go): **80**
- ▶ Recto verso: **STD**
- ▶ Caractéristiques du secteur - courant alternatif local calibré (Hz): **200-240V, 50/60Hz**
- ▶ Consommation d'énergie (kW): **1,84**
- ▶ Dimensions (mm): **645 x 670 x 960**
- ▶ Poids (Kg): **123**

## CHARGEUR DE DOCUMENTS

- ▶ Capacité chargeur (feuilles): **150**

## SERVEUR DE DOCUMENTS

- ▶ Serveur de documents (standard / option): **STD**
- ▶ Capacité du serveur de documents - dossiers principal et personnalisés: **1400**
- ▶ Capacité du serveur de documents - dossier temporaire: **1400**
- ▶ Travaux stockés: **Copy, print, scan, fax transmission**
- ▶ Dossiers de stockage: **Quick file folder, main folder, custom folder (max. 500)**
- ▶ Stockage confidentiel:

## FAX

- ▶ Fax (standard / option): **OPT**
- ▶ Méthode de compression: **MH/MR/MMR/JBIG**
- ▶ Protocole de communication: **Super G3**
- ▶ Temps de transmission (sec): **3**
- ▶ Vitesse du modem (bps): **33.600 - 2.400**
- ▶ Résolution de transmission: **203,2 x 97,8/406,4 x 391**
- ▶ Format du document (Min): **A5**
- ▶ Format du document (Max): **A3**
- ▶ Mémoire (Mo): **8**
- ▶ Niveaux de gris: **256**
- ▶ Enregistrement des numéros (express/abrévés): **999**
- ▶ Diffusion (max. destinations): **500**

## COPIEUR

- ▶ Format originaux (max.): **A3**
- ▶ Sortie première copie couleur (sec.): **6,9**
- ▶ Sortie première copie N&B (sec.): **4,7**
- ▶ Tri électronique standard:
- ▶ Copie continue (max. copies): **999**
- ▶ Résolution du scan N&B (dpi): **600 x 300**
- ▶ Résolution du scan couleur (dpi): **600 x 600**
- ▶ Résolution d'impression (dpi): **600 x 600**
- ▶ Niveaux de gris (équivalence) - N&B: **256**
- ▶ Niveaux de gris (équivalence) - Couleur: **256**
- ▶ Plage de zoom (%): **25-400**
- ▶ Taux de reproduction prédéfinis: **10**

## SCANNER

- ▶ Numérisation réseau (standard / option): **STD**
- ▶ Méthodes de scan 'Push' et 'Pull':
- ▶ Résolution du scan push (dpi): **100,200, 300,400, 600**
- ▶ Résolution du scan pull (dpi): **75,100, 150,200, 300,400, 600,50 to 9600**
- ▶ Formats de fichiers: **TIFF, PDF, encrypted PDF, JPEG (colour only)**
- ▶ Utilitaires de scan: **Network Scan Tool, Sharpdesk, Sharp Twain**
- ▶ Destination scan to PC:
- ▶ Destination scan to FTP, Email:
- ▶ Destination scan to SMB:
- ▶ Destination scan to clé USB:

## IMPRIMANTE EN RÉSEAU

- ▶ Résolution (dpi): **600 x 1200**
- ▶ Impression réseau (standard / option): **STD**
- ▶ Interface (standard / option): **STD USB 2.0, 10Base-T/100Base-TX**
- ▶ OS supportés en standard: **Windows 98/Me/NT4.0 SP5 or later/2000/Server 2003/XP/Vista**
- ▶ OS supportés en option: **Mac OS 9.0-9.2.2/Mac OS X 10.1.5/10.2.8/10.3.3-10.3.9/10.4 -10.4.10/10.5-10.5.1**
- ▶ Protocoles réseau: **TCP/IP, IPX/SPX (NetWare), NetBEUI, EtherTalk (AppleTalk)**
- ▶ Protocoles d'impression: **LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FTP for downloading print files, EtherTalk printing, IPP**
- ▶ Langues de description de pages (standard/option): **STD PCL6/5c, OPT PS3 emulation**
- ▶ Polices disponibles: **80 (PCL), 136 (PS3)**

## FINITION

- ▶ Capacité de sortie max.: **500 - 1000**
- ▶ Capacité d'agrafage (feuilles). Max.: **30 - 50**
- ▶ Piqûre à cheval: **OPT**
- ▶ Décalage: **OPT**
- ▶ Perforation: **OPT**

[www.sharp.fr](http://www.sharp.fr)

**SHARP**  
Be Original.

SHARP BUSINESS SYSTEMS FRANCE S.A.  
AVENUE DES NATIONS  
PARIS NORD II  
BP 52094  
95948 ROISSY-CHARLES-DE-GAULLE CEDEX  
TÉL. 01 49 90 34 00  
FAX 01 48 63 26 21  
[WWW.SHARP.FR](http://WWW.SHARP.FR)