[desktop-displays]

MultiSync E244F



Prioritising user comfort and delivering reliable performance, the E series is a perfect solution for the home office and small to medium sized businesses.

- Cost and time saving operation – based on an intuitive OSD design making set-up simpler.
- Ergonomic Office – full height adjustability (120 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Black and white colour versions – white is is considered to reduce the impression of tunnel vision when placed in front of a white background such as office walls.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, protecting users eyes.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

Spécifications

Technologie du panneau	VA TFT with W-LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m2)	250
Taux de contraste	3000:1
Taille de pixel (mm H x L)	0,249
Response Time (typ.) [ms]	6
Température de fonctionnement (oC)	5 to 35
Storage Temperature [°C]	-10 to 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Poids du produit sans le pied (Kg)	4
Poids du produit avec le pied (Kg)	6

Accessoires

Shipping Content	Cordon d'alimentation, Câble DisplayPort, Guide de configuration

Résolution

Optimum Resolution	1920 x 1080 at 60 Hz

Electrique

Power Supply	Integrated Power Supply

Conditions environnementales

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Mécanique

Taille du bézel (G/D) mm	3
Taille du bézel (B) mm	17

Caractéristiques supplémentaires

Colour Versions	Façade noir, Boîtier noir, Façade blanc, Boîtier blanc
Cable Management	Oui
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Prise casque jack
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free
Garantie limitée du fabricant (ans)	3 ans y compris rétro-éclairage
Montage (VESA/Nombre de points/Espacement mm)	100 x 100
Verrou Kensington	Oui

Affichage

Taille diagonale (cm)	22
Colours [Mio.]	16

Fréquence de synchronisation

Vertical Frequency [Hz]	50 - 75

Connectivité

Digital	DisplayPort, HDMI
Analog	D-sub 15 pin

Ergonomique

Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	541
[AVSpecificationLandscapeDimensionsHeightMm]	501
[AVSpecificationLandscapeDimensionsDepthMm]	233

Caractéristiques vertes

Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant

FLICKER-FREE TECHNOLOGY

LOW BLUE LIGHT TECHNOLOGY

NaViSet Administrator 2

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. MultiSync E244F, 8/9/2026