Écran de bureau

Sharp/ NEC MultiSync® E244FL



For driving down costs without compromising quality, the E-series prioritises user comfort and productivity making it an excellent solution for both the home office and for small to medium sized businesses for general office applications.

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

Spécifications

Technologie du panneau	VA TFT with W-LED backlight
Rapport d'aspect	16:9
Luminosité (cd/m2)	250
Taux de contraste	1000:1
Couleurs d'affichage	16.77
Temps de réponse (moy. gris à gris) ms	6
Taille de pixel (mm H x L)	0,275
Viewing Angle [°]	178
Température de fonctionnement (oC)	5 to 35
Storage Temperature [°C]	-10 to 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Poids du produit sans le pied (Kg)	5
Poids du produit avec le pied (Kg)	8

Accessoires

Shipping Content	Câble DisplayPort, Cordon d'alimentation, Guide de configuration, Câble USB-C

Résolution

Optimum Resolution	1920 x 1080 at 60 Hz

Connectivité

Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45

Ergonomique

Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507

Special Characteristics	Low Blue Light, Local dimming

Caractéristiques supplémentaires

Colour Versions	Façade noir, Boîtier noir, Façade blanc, Boîtier blanc
Cable Management	Oui
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Prise casque jack
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
Garantie limitée du fabricant (ans)	3 ans y compris rétro-éclairage
Montage (VESA/Nombre de points/Espacement mm)	100 x 100
Verrou Kensington	Oui

Affichage

Taille diagonale (cm)	24
Taille diagonale (cm)	60

Fréquence de synchronisation

Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75

Electrique

Consommation énergétique en fonctionnement (IEC62087:2012)	13 (Eco Mode 2), 19 (typ.)
Power Supply	Integrated Power Supply

Conditions environnementales

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Mécanique

Taille du bézel (G/D) mm	1
Taille du bézel (H) mm	16
Taille du bézel (B) mm	16

Caractéristiques vertes

Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant, TCO 9.0

NaViSet Administrator 2 · USB Type-C® · FLICKER-FREE TECHNOLOGY · LOW BLUE LIGHT TECHNOLOGY

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. Sharp/ NEC MultiSync® E244FL, 14/9/2026