[digital-signage-display]

Sharp MultiSync P556



Purpose-designed for control rooms, passenger information, and prestige retail or corporate signage, the P6 Series delivers uncompromising performance, day after day.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Spécifications

Technologie du panneau	IPS with Direct LED backlights
Rapport d'aspect	16:9
Luminosité (cd/m2)	700
Taux de contraste	8000:1
Temps de réponse (moy. gris à gris) ms	8
Taille de pixel (mm H x L)	0,315
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Surface d'écran active (H/L) mm	1209.6 x 680.4
Tension de fonctionnement (ACV) / Fréquence (Hz)	100-240
Tension de fonctionnement (ACV) / Fréquence (Hz)	50-60
Consommation énergétique (W) (Fonctionnement MAX)	115
Température de fonctionnement (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Storage Humidity [%]	10
Storage Humidity [%]	80
DisplayPort	1
Haze Level [%]	Pro 25
HDMI	2

Conditions environnementales

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Caractéristiques supplémentaires

Garantie limitée du fabricant (ans)	3 ans y compris rétro-éclairage
Special Characteristics	Simulation DICOM, CEC Support, HDMI ARC, Programmateur
Fonctionnement 24/7 certifié	Oui
Gradation locale	Oui
Gestion de l'alimentation	Oui
Emplacement pour équipements (Montage)	Oui
Détecteur de température	Oui
Détecteur de luminosité	Oui
Fonction de réduction de l'image résiduelle	Oui
Planification / Minuterie	Oui
Gestion à distance	Oui
Contrôle du gain	Oui
SNMP	Oui
Poids du produit sans le pied (Kg)	21
Poids d'expédition (kg)	27
Paysage	Oui
Portrait	Oui
Horizontal	Oui
Montage (VESA/Nombre de points/Espacement mm)	300 x 300 (FDMI)
Spécifications des vis de montage (Taille/Longueur maximale)	M6

Affichage

Taille diagonale (cm)	54
Taille diagonale (cm)	138

Mécanique

Taille du bézel (G/D) mm	11
Taille du bézel (H) mm	11
Taille du bézel (B) mm	14

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. Sharp MultiSync P556, 9/9/2026